

8660

S E R I E S

**CONCEALED
VERTICAL ROD
EXIT DEVICE**
*with INSET Push Bar
No Pinch - No Jamb!*

ANSI/BHMA GRADE 1 –
UL/ULC Listed for UL305
Panic Hardware

Suitable for Narrow, Medium,
and Wide Stile Doors¹

Standard Door Widths
36", 42", 48"

**48" width can be
trimmed down to 36"**

For widths less than 36"
Consult Factory



Standard 36" Device Shown
¹ Minimum stile size of 2".

Functions:

- Designed for simple prep and installation.
- Attractive low profile design with fully concealed fasteners.
- Extruded aluminum body in standard anodized finishes
- Field Reversible
- Hex key dogging standard.
- Device Projection of 3"

Options:

- **Electric Latch Retraction**
Motorized mechanism for fast, quiet operation capable of continuous duty.
- Interior Key Cylinder Dogging
- Signal Switch
- Alarm Board



**Inset Push Bar means
NO PINCH POINT!**

8660

S ■ E ■ R ■ I ■ E ■ S

No Visible
Fasteners
on Backside
of Device

PART NUMBERING

A/86B/C-D-E

SAMPLE NUMBER

MEL866036-CL-96

OPTIONS

(A) MISC. OPTIONS

MEL = Motorized Electric
Latch Retraction

AL = Alarm Board

SW = Signal Switch

CD = Cylinder Dogging

(B) FUNCTIONS

60 = Exit Only

61 = With 1" Round Offset
Pull (10" Centers)

62 = Prepped for Ext.
Key Cylinder

63 = Prepped for Ext.
Key Cylinder with
Cylinder Included

(C) DOOR WIDTH

36-48 = Number (inches)

XX = Special Width
(consult factory)

(D) FINISH

CL = Clear

BR = Dark Bronze

BL = Black

(E) SPECIAL HEIGHT

XX = (consult factory)