



# 8760

S ■ E ■ R ■ I ■ E ■ S

**RIM LATCHING  
EXIT DEVICE**  
*with INSET Push Bar*  
*No Pinch - No Jamb!*

ANSI/BHMA GRADE 1 –  
UL/ULC Listed for UL305  
Panic Hardware

Suitable for Narrow, Medium,  
and Wide Stile Doors<sup>1</sup>

Standard Door Widths  
36", 42", 48"

*48" width can be  
trimmed down to 36"*

For widths less than 36"  
Consult Factory



Standard 36" Device Shown  
<sup>1</sup> Minimum stile size of 2".

### Functions:

- Designed for simple prep and installation
- Attractive low profile design
- Extruded aluminum body in standard anodized finishes
- Non-handed
- Hex key dogging standard
- Device Projection of 3"

### Options:

- **Electric Latch Retraction**  
Motorized mechanism for fast, quiet operation capable of continuous duty.
- **Interior Key Cylinder Dogging**
- **Signal Switch**
- **Alarm Board**
- **Dead Latch**



Inset push bar means  
**NO PINCH POINT!**

Optional heavy duty,  
deadlatch

[www.FCBP.com](http://www.FCBP.com)


Phone (800) 793-4544 • Fax (800) 867-5016



# 8760

S ■ E ■ R ■ I ■ E ■ S

No Visible  
Hardware  
on Backside  
of Device



### PART NUMBERING

## A87B/C-D

SAMPLE NUMBER

## MEL876036-CL

### OPTIONS

#### (A) MISC. OPTIONS

MEL = Motorized Electric  
Latch Retraction

AL = Alarm Board

SW = Signal Switch

CD = Cylinder Dogging

DL = Dead Latch

#### (C) DOOR WIDTH

36-48 = Number (inches)

XX = Special Width  
(consult factory)

#### (D) FINISH

CL = Clear

BR = Dark Bronze

BL = Black

#### (B) FUNCTIONS

60 = Exit Only

61 = With 1" Round Offset  
Pull (10" Centers)

62 = Prepped for Ext.  
Key Cylinder

63 = Prepped for Ext.  
Key Cylinder with  
Cylinder Included

[www.FCBP.com](http://www.FCBP.com)

Phone (800) 793-4544 • Fax (800) 867-5016